

CAPXL CONNECTED ACCESS PORTAL, HIGH CAPACITY

Cloud-based access control for residential communities.



KEY FEATURES

COLOR TOUCH DISPLAY
10", 720p High-Def Interface

PLUG AND PLAY
Easy Setup and Programming

LIFTMASTER CLOUD™
Smart Access Control

SMART

INTUITIVE INTERFACE WITH COLOR TOUCH DISPLAY FOR SUPERIOR RESIDENT AND GUEST USABILITY.

CUSTOMIZABLE BACKGROUND ON A 10", FULL-COLOR, 720p HIGH-DEFINITION SCREEN.

REMOTE PROGRAMMING AND ACTIVITY MONITORING USING LIFTMASTER CLOUD.

AVOID TRENCHING WITH WI-FI® AND WIRELESS LINK TO LIFTMASTER® GATE OPERATORS.

RELIABLE

VOICE OVER IP (VoIP) PROVIDES CRYSTAL-CLEAR CALL QUALITY WITH NO LONG-DISTANCE CHARGES.

INSTANT EMAIL NOTIFICATIONS LET YOU KNOW IF THERE'S A PROBLEM BEFORE THE RESIDENTS.

STAINLESS STEEL FOR A MODERN, DURABLE DESIGN.

LOCAL DATABASE STORAGE ALLOWS RESIDENTS TO ENTER EVEN WHEN THE INTERNET IS DOWN.

SECURE

GET ALERTED WHEN A SUSPENDED CODE IS USED OR IF AN ACTIVE CODE IS BEING OVERUSED.

REAL-TIME ACTIVITY TRACKING WITH LIFTMASTER CLOUD.

CLOUD-BASED SECURITY KEEPS DATA PROTECTED AND SAFEGUARDS RESIDENT INFORMATION.

POWERFUL ADD-ONS:

CONNECTED ACCESS PORTAL, 2-DOOR CONTROLLER

Cloud-based, credentialed access control.



CAP2D

CELLULAR 4G/LTE MODEM WITH WI-FI®

Makes it easy to connect CAPXL and CAP2D(s) anywhere.



CAPCELL

TRIM KIT AND BACK KIT

Conceal openings left from other systems in flush-mount, infinity L and icon installations.



CAPXLTK

PASSPORT REMOTE CONTROLS

PPV3M/PPK3PHM/PPLK1-X
Visor and keychain remotes with unique credentialed IDs.



CAP2D

multiCLASS® SE RP10 MINI MULLION

Proximity reader for credentialed access.



LMMC-MINI

PROXCARD II® 1326 CLAMSHELL CARD

Proximity card for credentialed access.



LMPG2-ST

ELEVATOR ACCESS CONTROL

CAPB485/CAPDC485/CAPRELAY
Integrated elevator access and control.



CAP485

ANTENNA MOUNTING KIT

For extended remote control range or remote mounting.



WFAEXT

AUTO-CALL INPUT KIT

Connects a loop detector to CAPXL, initiating a phone call to a preconfigured number when a vehicle passes.



LPFX/LBFXKIT

MASTERFUL ENGINEERING.

CAPXL

CONNECTED ACCESS PORTAL,
HIGH CAPACITY

CAPACITIES



- 4 Controlled Gates/Doors
- Wireless Link for up to 8 LiftMaster® Operators
- 4 to 8 Digit Entry Codes
- 4 to 6 Digit Directory Codes
- 50,000 Local Resident Capacity
- 50,000 Local Event History
- Multiple, Holiday and Hold-Open Scheduling, Including One-Time and Repeating Exceptions

POWER



- Input 120V AC to 24V DC (Transformer Included)
- UL Listed
- Output 3 Amps

18"



MECHANICS




- 10", 720p High-Definition Touch Display
- Fade- and Glare-Resistant Display
- Outdoor Stainless-Steel Housing
- Built-In Security+ 2.0® Radio
- Postal Lock Provision
- Surface, Flush (CAPXLTK) or Pedestal (PED42, PED64) Mount
- Camera Ready; Use Any Standard Pinhole Camera



LiftMaster Cloud™

Have more entrances?
Add more CAPXLs or CAP2Ds
to meet the needs of
any community.



STANDARD SPECS.

ELECTRICAL

COMMUNICATION

INTERNET (DYNAMIC OR STATIC IP)

- Wi-Fi®
- High Speed
- DSL with at Least 1 MB Download Speed
- Cellular (Optional CAPCELL)

VOICE

- VoIP (Voice over IP)
- Phone.com® Service Required for VoIP

ONBOARD RADIO

- Security+ 2.0 for Passport Remote Controls
- Wireless Link to UL 325 Gate Operators Manufactured After October 2017
- Retrofit Kits Will Be Available for Operators Manufactured Between January 2016 and October 2017
- HomeLink® IV and V Compatible*

*Requires HOA or Management Assistance

WARRANTY

- 2-Year

INPUT PORTS

- 4 Wiegand Inputs
- 4 Request-to-Exit (REX) Inputs
- 4 Supervised Inputs
- 1 Auto-Call Input (Requires LPEXP)

OUTPUTS

- 4 Primary Relays
- 4 Auxiliary Relays
- 1 Wiegand Output

OPERATING TEMPERATURE **-20°F to 130°F**
(-29°C to 54°C)

SHIPPING.

SHIPPING WEIGHT (in lbs.)

24

CARTON (1)

- 23" x 18" x 9"
- CAPXL
- 24V DC Power Supply
- 2 Keys
- Radio Antenna
- Wi-Fi Antenna
- Misc. Hardware

For Support Tools and Training Videos, Visit LiftMasterTraining.com

For More Information, Visit LiftMaster.com/AccessControl

Sales Support: **800.282.6225**
Technical Support Center: **800.528.2806**
LiftMasterDealer.CustHelp.com/App/Ask