

TELEPHONE ENTRY / ACCESS CONTROL SYSTEM

EL2000



EXPANDED CAPACITY. ENHANCED VERSATILITY.

The EL2000 will change your expectations of what a telephone entry system should look like. The EL2000 is designed to complement virtually any gated community and is flexible enough to be used in apartment buildings, condo complexes, office parks and commercial sites.

The EL2000 features a 5-inch backlit LCD screen; the unit clearly displays up to 4 lines with 20 characters per line, making it a great choice for multi-tenant installations. The EL2000 is capable of accepting up to 2000 totally flexible codes. These codes can be programmed as directory codes or access codes, making the EL2000 ideal for virtually any installation. Unlike other systems,

the EL2000 may be purchased as a base unit or ordered with optional plug-in modules. This allows you to choose only the plug-in modules you need depending on the specifics of the job — enabling you to offer custom solutions right off the shelf without special orders.

LiftMaster®

EL2000

STANDARD FEATURES

Call Waiting

Allows a person to answer a call from the gate or door while in the middle of another outside call.

Recessed, Lighted, ADA-Compliant Keypad

Illuminated keys with help button assistance to audibly announce the next key press on the keypad.

Auto Sensor Input

May be set to automatically dial the residence when a vehicle approaches the property.

Distinctive Ringing

Provides double ring on the telephone line to distinguish visitor request call.

Entry Codes

2000 Programmable codes can be time-restricted or established as one-time use only.

Holiday Programming

Up to 16 separate holidays can be defined to override the standard lock/unlock schedules.

Time Zones

Up to 62 different time zones with three segments each can be created for access/no access schedules.

Anti-Passback

Timed anti-passback waits for a preprogrammed period of time to elapse before the code or card can be reused. True anti-passback requires use of an exit reader before entering again.

Security Lockout

Locks out all users for a programmable period of time if several invalid code attempts are made. Alarm can be set to activate if the gate or door is held open or forced open.

Postal Lock Provision

The EL2000 supports a switch kit that integrates with a U.S. Postal Service lock. This allows postal carriers entry to a controlled area using a U.S. Postal Service key.

Automatic Gate/Door Unlock Schedule

Entry points may be configured to automatically open or lock at set time periods.

Transaction Monitoring

A minimum of 4,000 transactions are stored in the unit including date, time, unit ID and transaction.

Activity Reports

Property managers have the ability to print database, system and history reports.

Remote Updates

System updates and upgrades may be made via remote computer over LAN, WAN, or a modem connection.

Completely Programmable Relays

4 assignable and programmable built-in relays

EXCLUSIVE FEATURES

Universal Board

The EL25 and EL2000 share the same main processing board, which makes it much easier to master the installation and service of both systems.

Remote Access Diagnostics

The EL2000 will retain unit alarms within the system event buffer. For added security, the unit will record the following alarms: forced door/gate and ajar door/gate. The EL2000 also records unit over voltage and under voltage alarms allowing for simplified troubleshooting of the system.

E-Z Scan

Cards and Passport™ transmitters can be programmed into the EL2000 simply by utilizing the card reader or radio receiver installed into one of the plug-in modules.

Voice Prompts

Guides installers through system setup at the unit's main keypad and provides assistance to end users with the push of a button. (ADA application)

Enhanced Line Noise Tolerance

A new, more robust main board allows the EL2000 to be more tolerant of noise associated with the older telephone company equipment, providing a better connection to the unit via modem.

Legacy Database Conversion

Replacing an existing Sentex® Telephone Entry System is a snap with Versa XS™ 2.0 software. Transfer any information retained in your existing Sentex® software database to Versa with the click of your mouse.

SPECIFICATIONS

Power

12V AC

Colors

Nickel, silver, gray

Mounting Styles

Portrait

Shipping Weight

25 lbs.

Dimensions



Voice Access Controllers

EL2000LB

LCD unit in black housing

EL2000LG

LCD unit in dark gray housing

EL2000LN

LCD unit in nickel housing

System Accessories

RFMODKT3

315 MHz RF module for remote access with Passport™ transmitters

WOMODKT

Wiegand module that supports two Wiegand compatible remote access devices

ESSWOKSG

Essex Wiegand compatible keypad - single gang mount

HIDWOKPRO

HID, Wiegand compatible combination keypad and proximity reader

ELHTRKT

EL2000 display heater

ELLCDKT

EL2000 LCD field kit

ELTRMKT

EL2000 trim plate kit

EL25CCAMKT

Color camera kit - 380 lines of resolution

EL25DVRCAMKT

DVR compatible low-lux color camera - 480 lines of resolution

Mounting Options

SNAPEDB

Gooseneck pedestal post (black)

PED42

42" pad mount, 2"x2" square black powdercoated pedestal

PED64

64" in-ground mount, 2"x2" square black powdercoated pedestal

1 YEAR WARRANTY

LiftMaster®

THE CHAMBERLAIN GROUP, INC.
845 Larch Avenue • Elmhurst, IL 60126

www.liftmaster.com



I.C./F.C.C.
Certified

