

PARKING

StrongArmPark™




Parking Barrier Arm

Ultra Reliable/Low maintenance • Millions of cycles • UPS standard • Field configurable

Is your barrier arm operator this Smart?

Thousand plus cycles after AC power loss*

Extremely low maintenance and minimal down time

Easy to configure numerous functions including parking specific options

Intelligent charging system monitors battery conditions to maximize battery life

Tested and listed by Intertek, a nationally recognized testing lab. Visit www.hysecurity.com for the significance of UL 325




Multi-Family Residential



Commercial



Corporate



* Actual UPS cycles depend on accessory power draw, frequency of cycles, battery health, ambient temperature and other conditions.

Advanced Breakaway Barrier Arm

Every StrongArmPark DC operator includes an advanced breakaway arm bracket, which reduces the cost of arm replacement due to a vehicle strike. The breakaway arm bracket adapts easily to typical aftermarket arms such as 1 x 4 inch wood or 2.5 inch square PVC.

HySecurity barrier arms:

- Custom PVC arms up to 10 ft (3 m) with LED lighting and bumper
- Custom aluminum arms up to 14 ft (4.3 m) with LED lighting and bumper
- Articulating arms with bumper, ideal for low clearance underground garages



Visit www.hysecurity.com

For specifications, tech support, pictures and email subscriptions

HySecurity[®]

Simple. Reliable. Secure.®

1-800-321-9947 • www.hysecurity.com

Highest Customer Satisfaction

Smart Barrier Arm

Distributed by:

See the latest from HySecurity at www.hysecurity.com



HySecurity operators secure the world's critical infrastructure and key assets where ultimate reliability is vital. **StrongArmPark DC** delivers that same uncompromising quality to commercial customers, where ease of use, consistent operation, low maintenance, long life and high reliability is expected.

For easy integration into parking systems, HySecurity offers a number of parking related relay options including an Extended Relay Module which adds eight output relays to the Smart DC Controller.

HySecurity strives for simplicity. Easy to install. Easy to configure. Easy to maintain. Easy to troubleshoot and repair. Your StrongArmPark DC barrier arm is built to last.

SMART DC CONTROLLER AND S.T.A.R.T. (Smart Touch Analyze & Retrieve Tool)

- Simplifies installation
- Configures gate operation to exact user needs quickly and easily
- Communicates in real time and stores faults in a date and time stamped log
- Simple, quick and inexpensive troubleshooting




Easily configure the operator with 5 tact buttons and a 32 character display. Faults flash on the display accompanied by an audio sequence which alerts owner. Faults can also be communicated in real time to the command and control network system for the ultimate in security. The 300 event fault log can be downloaded to a laptop computer to easily troubleshoot random events that appeared days in the past.

StrongArmPark DC™ Models

Standard	StrongArmPark DC 10	StrongArmPark DC 14
Solar 	StrongArmPark DCS 10	StrongArmPark DCS 14
Arm Length Capacity	10 ft (3 m)	14 ft (4.3 m)
Field adjustable Open/Close Time	3 speeds: 1.5/2/2.5 seconds	3 speeds: 2.5/3/3.5 seconds
Full Open Angle	Adjustable 90° ± 10°	
Handing	Left handing standard. Easy to convert to right handing in field	Left handing standard. Right handing available
Arm Designs	Custom PVC, Custom aluminum	Custom aluminum
	Articulating arm, 8 ft (2.4 m) or 9 ft (2.7 m) clearance, aluminum-PVC	n/a
	Brackets available for 1" x 4" (2.5 x 10 cm) wood and 2.5" (6 cm) square PVC	
Duty Cycle	Continuous	
UPS Battery Backup	Two 8 Ah batteries. Operates for thousand plus cycles after AC power loss.* Field configurable to fail open or secure when batteries deplete.	
Voltage Input	115VAC, 3A, 50/60 Hz, 208/230VAC, 1.5A, 50/60 Hz Solar: 24VDC solar panels	
Accessory Power	24VAC, 12VDC and 24VDC 1A each	
Temperature Rating	-13° F to 158° F (-25° C to 70° C) No heater necessary.	
Communication	USB, RS-232, RS-485	
User Controls	Smart DC Controller with 70+ configurable settings. 32 character LCD display and 5 tact buttons or a PC using S.T.A.R.T. software.	
Relays	Two configurable user relays: 30VDC, 3A solid state and 250VAC, 10A electromechanical.	
ETL Listed (UL 325)	Usage Class I, II, III, IV	
Warranty	2 years	

* Actual UPS cycles depend on accessory power draw, frequency of cycles, battery health, ambient temperature and other conditions.



OPTIONAL ACCESSORIES:

- Extended relay module provides eight additional relay outputs
- HY-5A intelligent vehicle detectors
- Photo eye

Compatible with most access control, safety, vehicle detection and other accessories.

SYSTEM DESIGN SUPPORT: Contact HySecurity for CAD drawings, installation information, technical manuals, help with custom site requirements or other support. Visit www.hysecurity.com or call to speak with a HySecurity representative today.