


# IHSL24UL / INSL24UL

24VDC Heavy-Duty Industrial Slide Gate Operator

---



**PRODUCT GUIDE**

**LiftMaster**

POWERED BY myQ

# IHSL24UL / INSL24UL

## 24VDC Heavy-Duty Industrial Slide Gate Operator

The LiftMaster® Heavy-Duty Industrial Slide Gate Operator builds on the brand's legacy of reliability. With the strength to effortlessly move 5,500-pound gates, the operator allows Facility Managers to focus on everyday responsibilities without worrying about failure or frequent maintenance. Easy to install, retrofit, program, and troubleshoot, it delivers worry-free continuous-duty operation—even in extreme weather conditions. The operator consistently lives up to the tireless demands of manufacturing, transportation, municipality, utility and warehouse environments. It also works as a complete system when paired with safety devices and offers full control over access points via myQ® technology.



### Popular features

#### Brushless DC Technology

Continuous-duty motor is more efficient and requires less maintenance, providing reliable DC performance 24/7.

#### Robust, Lockable Enclosure

14 ga. steel, weatherproof (NEMA 3R rated) cabinet prevents unauthorized access into the operator and protects it from the environment.

#### Pad and Retrofit Mounting Options

Optional riser (MRIN) makes it easy to replace an existing operator, providing multiple mounting positions and better protection from the climate.

#### Smooth Start/Stop Operation

Extends the life of the operator and gate hardware.

#### Battery Backup

Provides seamless operation by providing standby power when the power is down.

#### Industrial Grade Gear-Driven Transmission


Rugged and efficient performance for reliable operation, including Class III & IV applications.

#### Manual Disconnect

Lockable position allows gate to be opened manually when released.

#### UL® Listed

Gate operator and monitored safety protection devices are tested together to provide a robust, secure system.



**Motor**  
LiftMaster BLDC motor technology provides the power to move large gates

**Gearbox**  
LiftMaster's proprietary gearbox comes with low-friction gears for smooth operation and long-term durability

Connect and stay on top with myQ.



myQ Smart Facility Access is a cloud-based solution that keeps you up to date and in control of all of your facility's access points. This allows you to work smarter, improve efficiencies and reduce expenses.\*

## Included accessories

### S505AL

#### Monitored Small Profile Resistive Edge

Pressure-sensitive edge stops and/or reverses gate when sensing an obstruction in the pathway of a moving gate. Ideal for low-clearance applications, the S505AL is compatible with hardwired or wireless gate applications, in virtually any environment.



### LMRRUL

#### Monitored Retro-Reflective Photo Eye

Provide entrapment protection using this retro-reflective photo eye. The LMRRUL is equipped with a heater for harsh environments and is engineered with a wide beam for ease of alignment at installation; max. range: 50 ft.



## Recommended accessories

### Photo Eyes

Provide entrapment protection with photo eyes at your gate, with your option of retro-reflective or through-beam technology. LiftMaster Gate Operators come with weatherproof safety entrapment protection devices included, so you have a compliant system right out of the box.

### Edges

A safety edge stops and/or reverses a moving gate when sensing an obstruction in its pathway. Add the LMWEKITU to eliminate the need for wiring between LiftMaster Monitored Resistive Edges and Gate Operators.

### Loop Detectors/Loops

Loops prevent the gate from closing on a vehicle in its path by sensing a vehicle using loop wire that is installed in the ground. Add the LOOPDETLM detector, which plugs into the board for ease of installation.

### MRIN Riser Mount

Supports pad mounting and retrofit to SL585UL operators.

### Access

Always ensure a way in or out with access products, such as LiftMaster Remote Controls (811LMX). For full visualization of your access points in and out of your facility, connect your gate operator to myQ Facility.

\*When linked with an access control, Powered by myQ, cellular data or Wi-Fi® connection required. Test equipment regularly and follow safety instructions.

## Features

### Mechanics

- 24VDC Brushless DC motor drive
- Continuous-duty, high-cycle, high-temperature
- Industrial oil bath gearbox
- Chain: #50 IHSL24UL, #41 INSL24UL

### Power

- 120/230V single-phase
- 3PHCONV optional kit converts an input voltage of 208/230/460/575VAC to an output voltage of 120VAC
- Accessory power: 24VDC 1.0A output; switched and unswitched power

### Industrial-Grade Design

- Lockable steel cabinet, weatherproof (NEMA 3R rated)
- UL® usage classification: II, III and IV
- Operator weight: 129 lbs. (INSL24UL) 142 lbs. (IHSL24UL)

### Features

- Variable speed setting (0.5 ft./sec to 1 ft./sec)
- Easy to use manual disconnect
- LED diagnostic display: simplifies installation and troubleshooting
- Quick close and anti-tailgate quickly secure property, preventing unauthorized access
- Monitored safety inputs: 3 main board, 3 expansion board
- Programmable auxiliary relays: make adding additional features easy
- Security+ 2.0® on-board radio receiver: Up to 50 remote controls (unlimited with 811LMX/813LMX)
- Posilock® automatically closes the gate when it is pushed from the closed limit

Note: Not recommended for solar applications.

## Business partners

**For Sales** | 800.282.6225

**For Technical Support** | 800.528.2806

**For Billing** | 800.323.2276

**To Learn More** | [LiftMaster.com/UL325Gates](https://LiftMaster.com/UL325Gates)

### Slide Rating



### Battery Backup Operation

	7Ah Battery	33Ah Battery
Cycles	TBD	TBD
Standby Time	TBD	TBD

(cycles and standby time based on stand-alone system)

### Temperature

Without heater	-4°F (-20°C) – 140°F (60°C)
With heater (HTR)	-40°F (-40°C) – 140°F (60°C)

### Dimensions

Chassis	27.3" W (69.2 cm)	25.3" H (64.2 cm)	17.7" D (44.9 cm)
---------	----------------------	----------------------	----------------------

### Warranty

- 5 years commercial

### Carton contents

- Operator
- S505AL
- LMRRUL
- Chain – #50 IHSL24UL (25 ft.), #41 INSL24UL (30 ft.)
- Mounting Hardware
- Antenna