

CAP2D CONNECTED ACCESS PORTAL, 2-DOOR CONTROLLER

Cloud-based, credentialed access control.

POWERFUL ADD-ONS:



KEY FEATURES

CONTROLS
up to 2 Gates/Doors

EASILY EXPANDABLE
Network through
LiftMaster Cloud™

LIFTMASTER CLOUD
Smart Access Control

SMART

MULTIPLE-ENTRANCE CONTROL WITH LIFTMASTER CLOUD.

UNIVERSAL COMPATIBILITY WITH 26- AND 30-BIT
WIEGAND-COMPATIBLE READERS, RECEIVERS AND RFID READERS.

EXPANSIVE CAPACITY FOR 25,000 ACTIVE CREDENTIALS STORED LOCALLY
SO RESIDENTS CAN ENTER EVEN WHEN THE INTERNET IS DOWN.

REMOTE PROGRAMMING AND ACTIVITY MONITORING USING
LIFTMASTER CLOUD.

RELIABLE

EASY TO INSTALL IN NEW OR EXISTING PROPERTIES.

BACKED-UP STORAGE IN LIFTMASTER CLOUD ENSURES THAT
DATABASES ARE NEVER LOST.

POWER OVER ETHERNET (PoE) ALLOWS FOR FLEXIBILITY OF
DEVICE PLACEMENT.

SECURE

EMAIL ALERTS LET YOU KNOW WHEN A SUSPENDED CODE IS USED OR
IF AN ACTIVE CODE IS BEING OVERUSED.

REAL-TIME ACTIVITY TRACKING WITH LIFTMASTER CLOUD.

CLOUD-BASED SECURITY KEEPS DATA PROTECTED AND
SAFEGUARDS RESIDENT INFORMATION.

CONNECTED ACCESS PORTAL, HIGH CAPACITY

Cloud-based access control for
residents and guests.



CAPXL

CELLULAR 4G/LTE MODEM WITH WI-FI®

Makes it easy to connect CAPXL
and CAP2D(s) anywhere.



CAPCELL

PASSPORT RECEIVER

Proximity card reader compatible
with all standard Wiegand protocols.



PPWR

PASSPORT REMOTE CONTROLS

PPV3M/PPK3PHM/PPLK1-X

Visor and keychain remotes with
unique credentialed IDs.



KPR2000

WIRED KEYPAD AND PROXIMITY READER

Single-entry, multifunction controller
that supports up to 2,000 users.



multiCLASS® SE RP10 MINI MULLION

Proximity reader for
credentialed access.



LMC-MINI

PROXCARD II® 1326 CLAMSHELL CARD

Proximity card for
credentialed access.



LMP2-ST

MASTERFUL ENGINEERING.

CAP2D

CONNECTED ACCESS PORTAL,
2-DOOR CONTROLLER

CAPACITIES



- 2 Controlled Gates/Doors
- 25,000 Local Resident Capacity
- 6,000 Local Event History (FIFO) Offline from Host
- Multiple, Holiday and Hold-Open Scheduling, Including One-Time and Repeating Exceptions

POWER



- 12V DC, Min. 1.5 Amps (Transformer Not Included)
- PoE (802.3af) Enabled Network Devices, 13 Watts Max.
- UL Listed

MECHANICS



- Compact Size Mounts on Standard Single Electrical-Gang Box or in a NEMA Enclosure
- LED Indicator Lights Communicate Status

4"



3.5"

1.25"

Readers



CAP2D



LiftMaster Cloud™



CAPCELL or
Modem/Router

Have more entrances?
Add more CAPXLs or CAP2Ds
to meet the needs of
any community.

STANDARD SPECS.

ELECTRICAL

COMMUNICATION

INTERNET (DYNAMIC OR STATIC IP)

- High Speed
- DSL with at Least 1 MB Download Speed
- Cellular (Optional CAPCELL)

INPUT PORTS

- 2 Wiegand Inputs
- 2 Request-to-Exit (REX) Inputs
- 2 Supervised Inputs

OUTPUTS

- 2 Primary Relays
- 2 Auxiliary Relays

WARRANTY

- 2-Year

SHIPPING.

SHIPPING WEIGHT (in lbs.)



CARTON (1)

- 7 1/2" x 5" x 3"
- CAP2D
- Misc. Hardware

For Support Tools and Training Videos, Visit LiftMasterTraining.com

For More Information, Visit LiftMaster.com/AccessControl

Sales Support: **800.282.6225**

Technical Support Center: **800.528.2806**

LiftMasterDealer.CustHelp.com/App/Ask